

**iQ100, Wall-mounted Extractor Hood, 90 cm, clear glass black printed LC95KA670**



LA10LKA6 Standard odor filter

The wall-mounted chimney hood with high extraction rate – perfect for installing on the kitchen wall.

✓ LED light: For optimal visibility and atmosphere when cooking.



Typology: ..... Wall-mounted  
 Length electrical supply cord: ..... 130.0 cm  
 Height of the appliance: ..... 354 mm  
 Minimum distance above an electric hob: ..... 470 mm  
 Minimum distance above a gas hob: ..... 570 mm  
 Net weight: ..... 11.1 kg  
 Type of control: ..... Electronic  
 Number of speed settings: ..... 3  
 Max. air extraction: ..... 629 m³/h  
 Max. recirculation: ..... 230 m³/h  
 Number of lights: ..... 2  
 Noise level: ..... 67 dB(A) re 1 pW  
 Diameter of air outlet: ..... 150 / 120 mm  
 Grease filter material: ..... Washable aluminium  
 EAN code: ..... 4242003809556  
 Connection Rating: ..... 216 W  
 Fuse protection: ..... 10 A  
 Voltage: ..... 220-240 V  
 Frequency: ..... 50 Hz  
 Plug type: ..... GARDY plug w/ earthing  
 Installation typology: ..... Wall-mounted



## iQ100, Wall-mounted Extractor Hood, 90 cm, clear glass black printed LC95KA670

### Design:

### Operating and power:

### Power:

### Comfort and Safety:

### Comfort:

### Measures:

### Technical information:

- Energy Efficiency Class: C\*
- Average Energy Consumption: 94.5 kWh/year\*
- Blower Efficiency Class: D\*
- Lighting Efficiency Class: A\*
- Grease Filtering Efficiency Class: D\*
- Noise max. Normal Level: 67 dB\*
- 90 cm black Chimney hood with glass canopy
- black with glass canopy
- Glass plate clear glass black printed
- Suitable for ducted extraction and recirculation
- Recirculating kit
- Designed for wall mounted installation
- touch control with Electronic display
- 3 speed control
- Light Intensity: 377 lux
- Colour Temperature: 3000 K
- Metal grease filter with side extraction
- Filter cover glass
- Removable metal grease filters, dishwasher safe
- Maximum extraction 629 m<sup>3</sup>/h
- Noise level according to EN 60704-3 und EN 60704-2-13 at max. normal use exhaust air: 67 dB(A) re 1 pW (55 dB(A) re 20 µPa sound pressure)
- Dimensions exhaust air (HxWxD): 750-1080 x 896 x 386 mm
- Dimensions recirculating (HxWxD): 862-1080 x 896 x 386 mm
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Power rating: 216 W

\* In accordance with the EU-Regulation No 65/2014

**iQ100, Wall-mounted Extractor Hood, 90 cm, clear glass black printed LC95KA670**

